

**Postle Industries, Inc.**

Cleveland, OH USA

Phone: 216-265-9000

Fax: 216-265-9030

E-Mail: [sparky@postle.com](mailto:sparky@postle.com)

Web Site: [www.hardbandingsolutions.com](http://www.hardbandingsolutions.com)



## POSTALLOY® TUBE BANDING<sup>SM</sup> DURABAND® NC APPLICATION ON WORK STRING TUBING

**Duraband**, the most trusted name in drill pipe hardbanding protection since 2008, can also protect other oil and gas industry tubulars.

As well bores get deeper and horizontal laterals through shale formations extend their reach, the demands on work string tubing have grown exponentially. Extending the life of an asset is only a portion of the cost of managing this tubular. Shipping costs and downtime also impact the decision to protect work string tubing. TubeBanding with a single 1" (25mm) band of **Duraband** will help reduce torque and drag when drilling out frac plugs - especially in extended-reach and deviated well profiles.



**Duraband has been thoroughly tested and evaluated by independent testing authorities for application on work string tubing. Whether it is an application of Duraband on new work string tubing or re-application over existing hardbands (including competitive products) Duraband is the best choice to protect your tubular assets.**

### Why use Duraband® NC on your Work String Tubing?

- No cracks or porosity
- No spalling or separation from base material
- No Heat Affected Zone (HAZ) hardness issues
- It is applied with less heat-input
  - No distortion of threads (*Note: cannot be applied directly over threads*)
  - No dimensional changes in the connection due to warping
- No need to remove for re-application



[www.hardbandingsolutions.com](http://www.hardbandingsolutions.com)